

MB-LE110

The MetaBright™ LED Light Engine was designed for direct fiber coupling of up to 8mm fiber bundles and features advanced optical and thermal control technology as well as a built-in 24-volt constant current driver in one small compact package. LED Light Engines are typically used with optical fiber ring lights and backlights.



FEATURES

- Low power, high intensity spotlight source
- Optional mounting bracket available
- LED thermal management for stable performance
- Through-the-camera-lens illumination
- Flicker free performance and instant start up with Metaphase analog driver technology
- Built-in Constant Current Driver with 0-10VDC intensity control, compatible with DDC-3 and ILD-35 Dimmers

WAVELENGTHS

Order ID	Description / nanometers
W	White (6000K), Nominal
R	Red / 630nm
G	Green / 530nm
B	Blue / 470nm
IR850	Infrared / 850nm
IR05	Infrared / 1050nm
IR20	Infrared / 1200nm
IR30	Infrared / 1300nm
IR45	Infrared / 1450nm
IR55	Infrared / 1550nm
IR65	Infrared / 1650nm

GENERAL SPECIFICATIONS

Power Source:	24VDC ±5%
Cable (Standard):	10-foot cable with flying leads
Housing:	Black Anodized Aluminum
Ambient Temp:	-20°C to 40°C
Lifetime Expectancy:	75,000 hours (except UV)

MB-LE110

LED Light Engine							
MODEL	Length Inches (mm)	Lens Diameter Inches (mm)	Weight lbs (grams)	Cable QTY	Cable Length	Cable Description	Typical Input Current
MB-LE110	2.63 (66.7)	.25 (.64)	0.7 (320)	1	10ft	24 AWG 4 conductors	<.1 amps

Wiring (4 conductors, flying leads)**	
Wire Color	Function
RED	+24VDC
WHITE	0-10VDC INTENSITY CONTROL
BLACK	GROUND (24V RTN)
GREEN	SIGNAL GROUND

Wiring (4 conductors, without Intensity Control)	
Wire Color	Function
RED	+24VDC
WHITE	+24VDC
BLACK	GROUND (24V RTN)
GREEN	GROUND (24V RTN)

M12 (5 position male)**	
Pin #	Function
1	+24VDC
2	0-10VDC Intensity Control
3	GROUND (24V RTN)
4	SIGNAL GROUND
5	No Connection

The M12 connector option is not recommended for lights rated more than 4 amps

Wiring with ULC-2	
Wire Color	Function
RED, WHITE (+)	LED INPUT
BLACK, GREEN (-)	

Terminated within a 2 position ULC-2 output connector
(Phoenix Contact P/N: BCP-508-2)

**Note: The 0-10VDC Intensity Control input can accept voltages from 0-24VDC where the light will operate at full intensity in the 10-24VDC range. The light is proportionally dimmer for any Intensity Control voltage less than 10VDC and the light is OFF at approximately 0V or not connected (floating).

MB-LE110

PART NUMBER KEY								
MODEL	-	WAVELENGTH	-	DRIVER* (most common)	-	CABLE LENGTH	-	CONN.** (most common)
MB-LE110	-	XXXXX	-	XXXXXXXX	-	XXX	-	XXXX
MB-LE110		W (White 6000K, Nominal) R (Red 630nm) G (Green 530nm) B (Blue 470nm) IR850 (Infrared 850nm) IR05 (Infrared 1050nm) IR20 (Infrared 1200nm) IR30 (Infrared 1300nm) IR45 (Infrared 1450nm) IR55 (Infrared 1550nm) IR65 (Infrared 1650nm)		24Z 24NZ 24-ILD U ¹		5M 10M Length can be customized: ex. 7M=7meters Select or leave blank for 3 meters		M12D ^{1 2} Select or leave blank for flying leads
Example 1: MB-LE110-W-24Z Example 2: MB-LE110-IR30-24-ILD				¹ Not available in lights exceeding 4A input current ² Default cable length for an M12D connector is 19 inches				

Contact Metaphase Technologies or your local representative for options such as custom diffusers, lenses, polarizers, IP-rated enclosures for harsh environments, higher intensity, custom wavelengths, higher uniformity, etc. Not all options are available for all lights.

MB-LE110

Sample Part Number: **MB-LE110-W-24Z**

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
D	REVISED RELEASE	5/27/2016	

Metaphase Technologies, Inc. 211 Sinclair Road, Suite 100, Bristol, PA. 19007 215-639-8699 Fax 215-639-0977																			
QUANTITY: Per order	MATERIAL: See BOM	FINISH: Black Anodize	TREATMENT: N/A																
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="4">TOLERANCE/FINISH UNLESS OTHERWISE SPECIFIED</th> </tr> <tr> <th colspan="2">INCHES [MM]</th> <th colspan="2">SURF. FINISH</th> </tr> </thead> <tbody> <tr> <td>X</td> <td>X XX XXX</td> <td>[0.25] RMS</td> <td>[0.125] RMS</td> </tr> <tr> <td>[±.75]</td> <td>[±.25] [±.13]</td> <td>±.010</td> <td>±.005</td> </tr> </tbody> </table>		TOLERANCE/FINISH UNLESS OTHERWISE SPECIFIED				INCHES [MM]		SURF. FINISH		X	X XX XXX	[0.25] RMS	[0.125] RMS	[±.75]	[±.25] [±.13]	±.010	±.005	<small>THIS DOCUMENT IS THE PROPERTY OF METAPHASE TECHNOLOGIES, INC. WHOM MAY LOAN IT. SUBJECT TO RETURN UPON DEMAND. IT INCLUDES CONFIDENTIAL & PROPRIETARY INFORMATION WHICH MAY NOT BE DISCLOSED TO ANY THIRD PARTY, AND OR USED FOR ANY PURPOSE CONTRARY TO ITS INTENDED USE, WITHOUT THE EXPRESSED PRIOR WRITTEN CONSENT OF METAPHASE TECHNOLOGIES, INC.</small>	
TOLERANCE/FINISH UNLESS OTHERWISE SPECIFIED																			
INCHES [MM]		SURF. FINISH																	
X	X XX XXX	[0.25] RMS	[0.125] RMS																
[±.75]	[±.25] [±.13]	±.010	±.005																
APPROVAL SIGNATURE: _____ DATE: // /		TITLE: Top Assembly LE110 USED ON: Per customer SIZE: B DRAWING NUMBER: LE110 SCALE: 1:1 SHEET 1 OF 1																	

MB-LE110

Mounting Options:

Please contact your local Metaphase representative to learn more about mounting options for the MB-LE110.

MB-LE110 Mounting Bracket



COMPLIANCE



CONTACT US

Contact Metaphase Technologies at **215-639-8699** or your local representative for additional details, options and customizations.